**HIKVISION**®

# Better Connections for Better Workplaces

# Hikvision Network Switches

Whether you are in the office or working remotely, work with lightning-fast connections for all your devices – Hikvision switches make it happen.





Our switches fit in any of your workplaces and provide easy and reliable connectivity for small to medium-size offices, greatly enhancing your work efficiency.



### **Stable PoE Supply**

Support Power-over-Ethernet supply (on select models), making it easier to get networks up and running



### **Convenient Connections**

Quick connections with no configuration steps, boosting your efficiency



### **Adaptive Ports**

Enabling 10/100/1000 Mbps rates with stable and fluid transmission



### **Versatile Mounting Options**

Desktop and wall mounting available for a variety of installation scenarios



### **Silent Operation**

Enjoy a comfortable and noise-free working environment with the fan-less design

## **Product Showcase**







| Parameter              | DS-3E0105-O                     | DS-3E0108-O                     | DS-3E0116R-O                                |
|------------------------|---------------------------------|---------------------------------|---|
| Ports                  | 5 × 100 Mbps RJ45 port          | 8 × 100 Mbps RJ45 port          | 16 × 100 Mbps RJ45 port                     |
| MAC Address Table      | 1K                              | 2 K                             | 8 K   |
| Switching Capacity     | 1 Gbps                          | 1.6 Gbps                        | 3.2 Gbps                                    |
| Packet Forwarding Rate | 0.744 Mpps                      | 1.19 Mpps                       | 2.38 Mpps                                   |
| Shell                  | Metal material, fan-free design | Metal material, fan-free design | Metal material, fan-free design             |
| Mounting options       | Desk-and Wall-Mounting          | Desk-and Wall-Mounting          | Desk or rack installation and wall-mounting |
| Power Supply           | 5 VDC, 1A                       | 5 VDC, 1A                       | 220 VAC, 50/60 Hz                           |



| Parameter              | DS-3E0508P-O                              |  |
|------------------------|---|--|
| Ports                  | 4 × 1 Gbps PoE port, 4 × 1 Gbps RJ45 port |  |
| PoE Port               | Ports 1 to 4                              |  |
| Max. Port Power        | 30 W                                      |  |
| PoE Power Budget       | 60 W                                      |  |
| MAC Address Table      | 4 K                                       |  |
| Switching Capacity     | 16 Gbps                                   |  |
| Packet Forwarding Rate | 11.904 Mpps                               |  |
| Shell                  | Metal material, fan-free design           |  |
| Mounting options       | Desktop/Wall-mounted installation         |  |
| Power Supply           | 48 VDC, 1.35 A                            |  |



### **Headquarters**

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com











