



AX SERIES AXHUB



Description

The AX series wireless security hub supports 32 wireless inputs. It can communicate alarm and other important notifications over LAN, Wi-Fi, GPRS and 3G/4G to smart device applications and client software. The panel supports voice guided setup for configuration and operation, making the installation process quick and easy. This solution is mainly for residential and small commercial applications, such as housing, apartments, small shops and offices.

Main Features

- Supports dual path communication of alarm events and other signals over LAN, Wi-Fi, GPRS and 3G/4G utilising a main and backup channel
- Supports up to 32 wireless inputs, 32 wireless outputs, 8 keyfobs and 2 sirens
- Voice guide and setup for configuration and operation
- Wi-Fi Smart-Configuration
- Supports video verification
- Real time alarm report
- Long distance (800m in open area) two-way communication
- AES 128-bit data encryption of the wireless protocol

Specifications	
Wireless Inputs	32
Wireless Outputs	32
Users	12
Wireless Keyfob	8
Available RF Frequencies	Two-way wireless 433MHz & 868MHz
Wireless Siren	Max 2
User Notifications	Push Notifications, SMS, Voice
Built-in Proximity Reader	-xxR Supports up to 12 MIFARE card
Status LEDs	S: 1 Orange (Fault), 2 Green (Power, Cloud connect), 1 Red (Alarm), 1 Blue (Arming)
Tamper Protection	Front and rear tamper protection
Control via Smart device	Hik-Connect (available on both iOS and Android)
Panel Assist By	Voice prompt
On-board Rolling Video Buffer	Video Verification; 2ch (7 seconds, 5 seconds pre alarm, 2 seconds after alarm)
Multi Languages Optional	English, French, Russian, Italian, Spanish, Portuguese (upgrade via Cloud)
Interface	
Ethernet	10/100 Mbps Self-Adaptive Ethernet
GPRS	Supports Report Push-Notification to CMS, Cloud; Text notification via SMS; Audio notification via phone call (Models: -HG, -HGR)
3G/4G	Supports Report Push-Notification to CMS, Cloud; Text notification via SMS; Audio notification via phone call (Model: -HS)
SIM Card Slot	1 (Models: -HG, -HS, -HGR, -HSR)
Serial Port	1
Reset	1
Wi-Fi Protocol Standard	802.11b/g/n
Wi-Fi Security Encryption	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Protocol	
Hik SDK Protocol Compatible	Supports Hik-SDK, management on iVMS-4200
Smartphone Application	Hik-Connect
ARC Communication	SIA-DC-09; Contact ID
Web Server	For configuration via web browser
Mobile App	Supports Alarm Push-Notification, Arming/Disarming, Status Checking, Report Checking, Video Linkage
ONVIF Protocol	Supports third party IPC integration
Technical Specification	
Power Supply	Included 5VDC, 10W
Power Consumption	<5.6W
Backup Battery	1 Lithium battery, 3.8V, 4520mAh
Other Details	
Operating Temperature	-10°C to 55°C
Operating Conditions	10% to 90% humidity (Non-condensing)
Dimensions (WxHxD)	155 x 155 x 35mm
Colour	White or Black
Shell Material	PC+ABS

Available Models

- DS-PWA32-H, LAN+Wi-Fi
- DS-PWA32-HG, LAN+Wi-Fi+GPRS
- DS-PWA32-HS, LAN+Wi-Fi+3G/4G
- DS-PWA32-HR, LAN+Wi-Fi, Proximity Reader
- DS-PWA32-HGR, LAN+Wi-Fi+GPRS, Proximity Reader
- DS-PWA32-HSR, LAN+Wi-Fi+3G/4G, Proximity Reader

Distributed by

HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +6-032-7224000
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (0) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com

www.hikvision.com

Follow us on social media to get the latest product and solution information:



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



hikvisionhq



Hikvision Corporate Channel


www.hikvision.com



STYLISH DESIGN WITH COMPREHENSIVE CONNECTIVITY

The AXHub is the latest innovation in intruder alarm systems. Part of the Hikvision AX Series and catering for residential and small commercial applications, the AXHub connects security peripherals such as motion detectors and displacement sensors, alongside safety devices like smoke and gas sensors to keep people safe.

Simple to install and use, the AXHub provides voice prompts locally to assist during installation, as well as alert the end user to any events. The AXHub is also compatible with the Hik-Connect smart device app, in addition to a wide range of communication pathways and multipoint IP communications via either the Cloud or CMS for added peace of mind.



This Cloud connectivity allows full control of the system from anywhere via Hik-Connect, to easily and remotely arm, disarm and monitor the system. The Cloud also enables the use of revolutionary IVaaS (Intruder Verification as a Service), which allows end users and monitoring stations to quickly and efficiently confirm system events through HD video verification.

IVaaS (INTRUDER VERIFICATION AS A SERVICE)

This revolutionary service provides video verification (from any Hikvision or ONVIF IP camera in the premises) for users to quickly and efficiently confirm an alarm event on the system.


During the configuration of the panel, 2 cameras can be linked to the AXHub, which incorporates a **rolling video buffer**. Where other video verification methods rely on sending low-quality static images to confirm events, IVaaS utilises Cloud technology alongside the buffer to **link previously separate video and intruder systems to one platform**. This provides a 7 second clip in the event of an alarm; **5 seconds pre-alarm and 2 seconds post-alarm**.

As a result, Hikvision cameras and the AXHub alarm systems work seamlessly together to provide a recorded video clip or live HD video footage, directly through Hik-Connect, iVMS or instantly to monitoring stations. This allows active decisions to be made faster and more reliably in the event of an activation.

IVaaS also provides alarm and push notifications, remote arming and disarming, and viewing live and recorded camera feeds.




KEY FEATURES



HIK-CONNECT

The end user app, Hik-Connect, brings together intrusion and video like never before. Linking detectors and sensors to cameras for video verification, as well as providing the end user with the ability to monitor the system from anywhere in the world; remotely checking system status, receiving alerts, arming, disarming, HD video monitoring and more, to remain informed and in complete control at all times.



WEB CONFIGURATION

The AXHub has a built-in web server which enables the device to be configured through a web browser over the local IP network. This offers more flexibility and time saving on site, as setup can be done quickly and efficiently using a laptop or compatible smart device.



TWO-WAY WIRELESS DEVICES


With the AXHub, you can add up to 32 two-way wireless devices. This provides a system which is secure and flexible; allowing even larger premises to be secured with a wide range of indoor and outdoor Hikvision peripherals.

LONG DISTANCE


The high sensitivity receiver utilised with two-way wireless technology allows a wireless signal range of up to 800m in open space, which ensures signals are as strong as possible, while eliminating the need for repeaters; reducing the installation costs.

IVaaS options:

Option 1: Recorded Push Message with Rolling Video Buffer
Connect up to 2 IP cameras directly to the AXHub



Option 2: Live Video
Live HD Video via Hik-Connect



*Hikvision and ONVIF cameras can be linked directly with the AXHub.



MULTIPLE COMMUNICATION PATHS

The variety of communication pathways available with the AXHub is unmatched. It offers LAN, Wi-Fi, GPRS and 3G/4G connections with on-board communication modules and connectors for a simpler and more cost-effective installation. With multipoint IP communications, the AXHub can also communicate simultaneously with multiple devices, to ensure alarm messages are sent to all that need them.



EASY SETUP AND INSTALLATION

Setting up the system could not be simpler, with an intuitive and easy to use interface. Connect to the panel directly via our web-browser or with iVMS-4200 on a laptop for on-site setup or, alternatively, program the system using the Hik-Connect app. Learning devices and sensors onto the system is also easy using the one-push-to-learn feature on all Hikvision wireless intrusion devices, to save time and money.



ARC LINKAGE

If ARC connectivity is required, the AXHub can communicate alarms and other messages in Contact ID format for a rapid and efficient response.