

Hook Lock and Digital Lock Kit

Specification Sheet
HLDK/HLSK

FEATURES

- Secure: Hook and pin prevents gates being opened when locked.
- Designed for use on sliding gates which needs to be latched shut for security.
- Double-sided or single-sided versions available (double-sided version allows the deadlocking of the hook for extra security).

PRODUCT DETAILS

Product code	Description
HLSK30	30mm (1-1/8") box section, single-sided
HLSK40	40mm (1-5/8") box section, single-sided
HLSK50	50mm (2") box section, single-sided
HLDK30	30mm (1-1/8") box section, double-sided
HLDK40	40mm (1-5/8") box section, double-sided
HLDK50	50mm (2") box section, double-sided

Lock Size:	108 x 275mm, choice of three widths (30mm, 40mm and 50 mm)
From center of eurocylinder to front of box:	65mm



INCLUDED IN THE BOX

- Hook lock
- Eurocylinder
- Pair of digital keypads
- A set of keys (3)
- Fixings

INSTALLATION

1. Cut out a section of the box section on the gate and weld-in the steel case in its place.
2. Galvanise or pain the gate with the lock built in.
3. Fit the hook lock and digital keypads with the fixings provided.

Please note:

If you need to change the handing of the hook lock you can remove the keypads and swap them round.