

Q1 Providence | East Bank Demerara | Tel: +592-265-7445

45 Urquhart Street | Georgetown | Tel: +592-226-8130

Email: info@fmlgy.com

Visit us at WWW.FMLGY.COM



GENERATORS



LC2500-AS

Compact and reliable, this generator is powerful enough to run lights, a small fridge, a fan a microwave oven or a TV, and is ideal for leisure use, for camping or caravanning being portable and sturdy.

Engine Type Single cylinder,4

stroke, forced cooling,

OHV

Max Output 2200w

Rated Output 2000w

Rated Voltage 110V/115V/120V/220V/

230V/240



LC3500-AS

This fantastic generator has a fuel capacity of 18 litres and a rated output of 2.8kw (230V) of continuous power. It reduces fuel consumption by up to 25% making it incredibly economical as well as reliable.

Engine Type G210FA/G210FAD

Single cylinder, 4T forced air cooled,

212cc

Max Output 2200w

Rated Output 2000w

Rated Voltage 110V/115V/120V/220V/

230V/240

Contact us for more options



A CROSBIE

MEMBER COMPANY

Email: info@fmlgy.com Visit us at WWW.FMLGY.COM



GENERATORS



LC5000-AS

The Loncin LC5000D-AS petrol AVR generator has been designed for industrial applications and home backup use.

Engine Type Loncin G340F engine,

337cc, single-cylinder

Max Output 4000

Rated Output 4000

Rated Voltage 230V /115V



LC6500-AS

The LC6500-A Power Generator, with a maximum power of 5500W, has been designed and assembled by LONCIN, one of the largest and most quality manufacturers of gasoline engines and gasoline-powered generators in the world.

Engine Type Engine type Single

cylinder 4-stroke, OHV

Max Output(KW) 5.5

Rated Output(KW) 5

Rated Voltage 230V /115V

Contact us for more options





GENERATORS



LC8000-AS

The Loncin LC8000D-AS petrol AVR generator has been designed for industrial applications and home backup use.

Engine Type G420F, 420cc

Max Output 6000

Rated Output 6000

Rated Voltage 230V /115V



LC10000-AS

LC10000D-AS framed generator set is powered by a strong commercial grade Loncin LC193F 459cc single cylinder 4 stroke forced cooling OHV engine.

Engine Type LC193F 459cc single

cylinder, 4 stroke, forced

cooling OHV engine

Max Output 8000

Rated Output 7300

Rated Voltage 230V /115V

Contact us for more options





PUMPS



lc25ZB36-1.2Q

Loncin make durable and reliable engines and pumps, and if you need to remove water from a flooded basement kitchen, empty a swimming or paddling pool, or many other kinds of domestic fluid removing work, this model is ideal. It delivers 8000 litres per hour, with Loncin's easy-to-start, reliable LC152F, 1.6hp, 97cc engine providing the power.



LC50ZB30-4.5Q-1

The Loncin LC50ZB30-4.5Q5 2 Inch Petrol Powered Water Pump is suitable for all manner of mid to large-scale domestic applications as well as use on farms and small construction sites. It delivers 30000 litres per hour, using Loncin's easy-to-start, reliable Loncin G160F 4.8hp 163cc Tier 5 compliant engine with fuel saving OHV technology for smoother performance and environmentally friendly emission volumes.



LC50ZB60-4.5Q-2

A compact but highly practical high-lift pump, suitable for domestic and light industrial use, High lift pumps are ideal for moving water from low areas like underground tanks, deep pools, wells and similar and this model has a 2" inlet and outlet pipe with a maximum lift of around 60 metres, maximum suction of 6 metres and a handy delivery volume of 30,000 litres an hour.

Contact us for more options



A CROSBIE

MEMBER COMPANY

Email: info@fmlgy.com Visit us at WWW.FMLGY.COM

LEO®

PUMPS



Applicable in water supply and drainage for factories, mines, municipal facilities as well as field irrigation, etc.

Max Flow 132 GPM
Max Head 30m
Max suction 8m

Inlet/Outlet 2" (50mm)

Engine Single cylinder, 4 stroke,

Air-cooled

Displacement 163cc/5.5HP



LEO LGP30-B

Applicable in water supply and drainage for factories, mines, municipal facilities as well as field irrigation, etc.

Max Flow 264GPM Max Head 30m Max suction 8m

Inlet/Outlet 3" (75mm)

Engine Single cylinder, 4 stroke,

Air-cooled

Displacement 163cc/5.5HP



LEO LGP30-W

The gasoline sewage pump is used to transfer slurry, as well as liquids that contain mud, sand, small rocks and other debris at a diameter less than 22mm.

Max Flow 220GPM
Max Head 25m
Max suction 8m

Inlet/Outlet 3" (75mm)

Engine Single cylinder, 4 stroke,

Air-cooled

Displacement 196cc/6.5HP



Contact us for more options



A CROSBIE

MEMBER COMPANY Q1 Providence | East Bank Demerara | Tel: +592-265-7445 45 Urquhart Street | Georgetown | Tel: +592-226-8130

Email: info@fmlgy.com Visit us at WWW.FMLGY.COM