



**LENTUS**

# **POWER TRANSMISSION & MRO**



**DUPONT**

**DOWSIL™**

**DOWFROST™**

**FROTH-PAK™**

**GREAT STUFF**

**LUCAS OIL**



[LentusLLC.com](http://LentusLLC.com)

[Sales@LentusLLC.com](mailto:Sales@LentusLLC.com)

+1-270-765-2212

400 Ring Road, Suite 101  
Elizabethtown, KY 42701

# Table Of Contents

Lentus History	3
DOWSIL™ Sealants	4
Dow Propylene Glycols	7
DOWSIL™ Primer & Coats	8
SILASTIC™ Mold-Making	9
DOWSIL™ Specialty Fluids	10
GREAT STUFF™ Work Wipes & Gloves	11
GREAT STUFF™ Foams	12
FROTH-PAK™ Foams	12
LENTEK™ Foam Sealants	13
Lucas Oil	14



**DOWSIL™**

**DOWFROST™**

**LUCAS OIL**



**GREAT STUFF™**

**FROTH-PAK™**



While Lentus strives to make the information in this catalog as timely and accurate as possible, we makes no claims or guarantees about the accuracy, completeness, or adequacy of the contents, and expressly disclaims liability for errors and omissions in the content of this catalog.

# LENTUS HISTORY

1965

Jim Hartlage (Lentus Founder) began working as a Lab Technician for Dow Corning in Elizabethtown, KY

1970

Jim founded Accumetric, the first authorized repackager of Dow Corning Silicone Sealants

2011

Dow, formerly known as Dow Corning, approached Jim and Jud Hartlage (Lentus President) to become Master Distributor for Dow Silicones

2012

**Lentus was Founded on July 1**



## DOWSIL™ 732 Multi-Purpose Sealant

One-component, acetoxy-cure adhesive sealant engineered for general industrial sealing and bonding applications.

Features extensive technical specifications for more-regulated applications.

- Non-sag, paste consistency
- Easy to apply
- Cures to a tough, flexible rubber
- Good adhesion to many substrates
- Meets MIL-A-46106, FDA Reg 21 CFR 177.2600, NSF 51, and NSF 61 requirements
- UL Listed
- Available in 90 mL, 139 mL, 300 mL, 17.7 KG, and 205 KG

PART Nº	SIZE	COLOR	CASE / PALLET
1891961	90 mL	Aluminum	12 / 3,000
99179259	300 mL	Aluminum	12 / 1,296
2112531	90 mL	Black	12 / 3,000
99179209	300 mL	Black	12 / 1,296
3138356	90 mL	Clear	12 / 3,000
99179271	300 mL	Clear	12 / 1,296
3140717	90 mL	White	12 / 3,000
99179246	300 mL	White	12 / 1,296



## DOWSIL™ 733 Glass & Metal Sealant

Conventional one-part, acetoxy RTV designed for use in OEM bonding and sealing applications, including appliances, heavy equipment, recreational vehicles, and marine equipment. Also excels in general industrial sealing and bonding applications.

- Enhanced unprimed adhesion to cleaned substrates including glass, metals, and plastics
- Good resistance to weathering, vibration, moisture, ozone, and extreme temperatures
- Easy to apply
- Meets MIL-A-46106, FDA Reg 21 CFR 177.2600, NSF 51, and NSF 61 requirements
- UL Listed

PART Nº	SIZE	COLOR	CASE / PALLET
99179264	300 mL	Aluminum	12 / 1,296
99179189	300 mL	Black	12 / 1,296
99179322	300 mL	Clear	12 / 1,296
2468379	17.7 KG	Clear	1 / 24
99179245	300 mL	White	12 / 1,296
2468336	17.7 KG	White	1 / 24



## DOWSIL™ 700 Industrial Grade Silicone Sealant

Designed for general industrial sealing and adhesive applications. Cost-effective alternative to DOWSIL™ 732 for less regulated applications.

- One-part room temperature cure
- 100% silicone, free of any petroleum distillates
- Resistant to weathering and adverse conditions
- Ideal for caulking, bonding, adhering, and formed-in-place gasketing
- Meets FDA Reg 21 CFR 177.2600 and NSF 51 food contact requirements
- UL 94 HB Compliant (low-flammability)

PART Nº	SIZE	COLOR	CASE / PALLET
4060123	300 mL	Aluminum	12 / 1,296
4060067	300 mL	Clear	12 / 1,296
4060071	17.4 KG	Clear	1 / 24
4060070	205 KG	Clear	1 / 4
4060069	300 mL	Black	12 / 1,296
4060122	17.4 KG	Black	1 / 24
4063559	205 KG	Black	1 / 4
4060068	300 mL	White	12 / 1,296
4066044	205 KG	Red	1 / 4





## DOWSIL™ 737 Neutral Cure Sealant

Neutral, oxime-cure RTV adhesive/sealant with primerless adhesion to most substrates. In addition to typical bonding/sealing applications, can also be used to replace mechanical fasteners and waterproof electrical components.

- Oxime cure (neutral)
- Primerless adhesion to a wide variety of substrates
- UV and weather resistant
- Low odor and non-corrosive to metals and alkalines when compared to alkoxy-based RTVs
- UL 94 HB Compliant (low-flammability)

PART N°	SIZE	COLOR	CASE / PALLET
99180484	300 mL	Black	12 / 1,296
4099910	17.6 KG	Black	1 / 24
4098499	90 mL	Clear	12 / 3,000
99180483	300 mL	Clear	12 / 1,296
4098497	17.6 KG	Clear	1 / 24
4098496	205 KG	Clear	1 / 4
99180646	300 mL	White	12 / 1,296
4099876	17.6 KG	White	1 / 24



## DOWSIL™ 734 Flowable Sealant

Designed for general industrial sealing and bonding applications requiring a flowable, self-leveling product. Particularly suitable for sealing assemblies with fine joints as well as cable entries and connectors to ensure they remain watertight.

- Flowable and self-leveling
- Cures to a tough, flexible rubber at room temperature
- Easy to apply, one-part acetoxy cure
- Meets MIL-A-46106, FDA Reg 21 CFR 177.2600, and NSF 51 requirements
- UL Listed

PART N°	SIZE	COLOR	CASE / PALLET
4102963	90 mL	Clear	12 / 3,000
99179310	300 mL	Clear	12 / 1,296
4102353	18.1 KG	Clear	1 / 24
4101950	204.1 KG	Clear	1 / 4
4102964	90 mL	White	12 / 3,000
99179270	300 mL	White	12 / 1,296
4102341	18.1 KG	White	1 / 24



## DOWSIL™ 736 Heat Resistant Sealant

Non-slumping sealant designed for sealing and bonding applications exposed to temperatures as high as 600° F. Ideal for sealing and encapsulating heating elements in appliances, aerospace gasketing, moving oven belts, and bag filters on smoke stacks.

- One-component silicone that will not sag or run
- May be applied overhead or on side walls
- Designed to meet MIL-A-46106 Rev. B Spec
- Meets FDA Reg 21 CFR 177.2600 and NSF 51 requirements
- UL 94 HB Compliant (low-flammability)

PART N°	SIZE	COLOR	CASE / PALLET
2423472	90 mL	Red	12 / 3,000
99179248	300 mL	Red	12 / 1,296
3145824	17.7 KG	Red	1 / 24
4023912	205 KG	Red	1 / 4



## DOWSIL™ 738 Electrical Sealant

One-part, white, non-flowing RTV designed for the bonding and sealing of electrical assemblies.

- Room temperature cure when exposed to moisture
- High elongation for added stress relief
- Faster in-line processing with optional heat acceleration
- Non-flowing
- UL Listed

PART Nº	SIZE	COLOR	CASE / PALLET
1949101	90 mL	White	12 / 3,000
99180508	300 mL	White	12 / 1,296
1907824	17.6 KG	White	1 / 24



## DOWSIL™ 786 Silicone Sealant

Silicone rubber sealant for nonporous surfaces, showers, tubs, sinks, and plumbing fixtures where conditions of high humidity and temperature extremes exist. Excellent as ceramic tile grouting.

- Cured sealant is mildew-resistant
- Remains permanently flexible without shrinking, cracking, crumbling, or drying out
- Resists staining, spotting, or color changes
- Meets FDA Reg 21 CFR 177.2600 and NSF 51 requirements

PART Nº	SIZE	COLOR	CASE / PALLET
99179247	300 mL	Clear	12 / 1,296
99179249	300 mL	Trans White	12 / 1,296
99179321	300 mL	White	12 / 1,296
4011651	17.7 KG	White	1 / 24



## DOWSIL™ 832 Multi-Surface Adhesive Sealant

Neutral-cure RTV adhesive sealant featuring an adhesion promotor that provides excellent adhesion to many substrates.

- Superior unprimed adhesion to a wide variety of substrates, including glass, metal, masonry, concrete, and most rubber and plastics
- Low odor
- Neutral alkoxy (alcohol-based) cure
- Non-corrosive to metals and other corrosion-sensitive materials
- UL Listed

PART Nº	SIZE	COLOR	CASE / PALLET
99180523	300 mL	Black	12 / 1,296
4059470	22.7 KG	Black	1 / 24
99180620	300 mL	Gray	12 / 1,296
2654580	22.7 KG	Gray	1 / 24
2823501	228.1 KG	Gray	1 / 4
99180648	300 mL	Off-White	12 / 1,296
4031452	22.7 KG	Off-White	1 / 24



## DOWFROST™ Heat Transfer Fluid

- Industrially inhibited heat transfer fluid with an operating range of -50°F to 250°F (-46°C to 121°C)
- Made with pharmaceutical grade DOW PuraGuard™ Propylene Glycol USP/EP
- Provides freeze protection to below -60°F (-51°C) and burst protection to below -100°F (-73°C), depending on concentration
- NSF Registered for use where there is possibility of incidental food contact
- Clear DOWFROST is Generally Regarded As Safe (GRAS) by the FDA
- Available in blue and clear in 1 gal bottles, 5 gal pails, 55 gal drums, and 265 gal totes

### Applications

- HVAC
- Chill water and hydronic heating loops
- Geothermal
- Snow melt, defrosting, and turf heating
- Solar hot water heating
- Fire water sprinkler systems
- Food processing
- Chilling of dairy products and beverages
- Cold room dehumidifying
- Beer and wine (fermentation cooling)
- Refrigeration and freezing
- Ice skating rinks
- Secondary heat transfer loops



## DOWFROST™ HD Heat Transfer Fluid

- Engineered for closed loop HVAC systems with operating range of -50°F to 325°F (-46°C to 163°C)
- Made with pharmaceutical grade DOW PuraGuard™ Propylene Glycol USP/EP
- Provides freeze protection to below -60°F (-51°C) and burst protection to below -100°F (-73°C), depending on concentration
- Contains industrial corrosion inhibitors and yellow dye for leak detection
- Available in 1 gal bottles, 5 gal pails, 55 gal drums, and 265 gal totes

### Applications

- HVAC
- Chill water and hydronic heating loops
- Geothermal
- Snow melt and turf heating systems
- Solar hot water heating
- Fire water sprinkler systems
- Refrigeration
- Ice skating rinks
- Large-scale chiller systems
- Cold storage, refrigerated warehouses, and supermarkets (secondary loop)
- Thermal Energy Storage (TES)



## DOWCAL™ 200 Heat Transfer Fluid

- Provides long lasting and efficient corrosion protection, particularly for aluminum alloys
- Low acute oral toxicity
- Free of nitrite, borax and CMR (carcinogenic, mutagenic and reprotoxic)
- Recommended operating temperature range between -50°F to 350°F (-46°C to 121°C)
- Long fluid lifetime, lowering maintenance cost
- Available in 1 gal bottles, 5 gal pails, 55 gal drums, and 265 gal totes

### Applications

- Solar heating
- Floor heating
- Snow melting systems
- Process heating
- Heat recovery
- Cooling of electronic systems and components
- Wind turbine systems
- Photo-voltaic (PV) inverters
- Data center cooling
- Ice skating rinks



## DOWSIL™ 1200 OS Primer

An air drying primer supplied as a dilute solution of moisture reactive materials in volatile siloxane. Used to improve both the quality and speed of adhesion development to room temperature vulcanizing silicone sealants to a variety of common non-porous substrates.

- Useful for both moisture-curing RTV, and heat-curing silicones
- Diluted in low-molecular-weight silicone fluid
- Meets many international regulations for low VOC content
- Enhances bonding/adhesion of RTV and heat-cure silicones to ceramics, glass, wood, masonry, structural plastics, and many metals

PART Nº	SIZE	COLOR	CASE / PALLET
4099614	309 G Can	Clear	6 / 100
4099615	2.9 KG Pail	Clear	1 / 60



## DOWSIL™ PR-1200 RTV Prime Coat

Clear, naptha based general purpose primer for use with all silicone elastomers and RTVs. It also promotes adhesion of certain one-part silicone sealants and coating to a variety of construction materials such as plywood, masonry, and metal.

- Significantly improves the adhesion of silicone sealants to a wide variety of challenging substrates
- Available in clear and red
- Improves the adhesion of silicone sealants, coatings, and rubber to masonry, wood, granite, metals, glass, ceramics, plastics, rubbers, and coatings

PART Nº	SIZE	COLOR	CASE / PALLET
4094479	309 G Can	Clear	6 / 100
4094480	2.9 KG Pail	Clear	1 / 60
4093873	160 KG Drum	Clear	1 / 4
4094481	309 G Can	Red	6 / 100
4094512	2.9 KG Pail	Red	1 / 60



## DOWSIL™ PR-2260 Prime Coat

Dilute solution of silane coupling agents and other active ingredients used in adhesion enhancing; light straw colored primer dispersed in heptane for use with RTV and heat cure silicones.

- Enhances bonding/adhesion of RTV and heat cure silicones to many metals, ceramics, and some plastics

PART Nº	SIZE	COLOR	CASE / PALLET
4094470	340 G Bottle	Clear	1 / 90
4094468	2.7 KG Pail	Clear	1 / 60
4094469	13.6 KG Pail	Clear	1 / 60
4094471	136 KG Drum	Clear	1 / 4





## SILASTIC™ RTV-3110 Mold-Making Base

General purpose low viscosity silicone mold making rubber suited for the reproduction of objects with no deep undercuts or complex shapes. Can be used in electronic potting and encapsulating applications.

- Two-part RTV silicone rubbers
- Low mixed viscosity
- Adjustable cure times
- Easy to use
- Reproduce intricate details
- Works in a wide range of service temp

PART Nº	SIZE	COLOR	CASE / PALLET
4107656	453 G Bucket	Off-White	24
4107661	4 KG Pail	Off-White	1 / 10
4107665	18.1 KG Pail	Off-White	1 / 24
4134209	181.4 KG Drum	Off-White	1 / 4



## SILASTIC™ RTV-3120 Mold-Making Base

General purpose low viscosity silicone mold making rubber suited for the reproduction of objects with no deep undercuts or complex shapes. Can be used in electronic potting and encapsulating applications.

- Two-part RTV silicone rubbers
- Low mixed viscosity
- Adjustable cure times
- Easy to use
- Reproduce intricate details
- Works in a wide range of service temp

PART Nº	SIZE	COLOR	CASE / PALLET
4107663	453 G Bucket	Off-White	24
4107664	4 KG Pail	Off-White	1 / 10
4107666	18.1 KG Pail	Red	1 / 24
4107672	181.4 KG Drum	Red	1 / 4



## SILASTIC™ RTV-3010-S Catalyst

Catalyst used for RTV-3 Series silicone moldmaking rubbers.

- Two-part RTV silicone rubbers
- Low mixed viscosity
- Adjustable cure times
- Easy to use
- Reproduce intricate details
- Works in a wide range of service temp

PART Nº	SIZE	COLOR	CASE / PALLET
4107697	45 G Tube	Light Blue	24 / 2,400
4107699	409 G Bucket	Light Blue	4 / 2,160
4107698	1.8 KG Pail	Light Blue	1 / 36
4107700	18.1 KG Pail	Light Blue	1 / 36



## DOWSIL™ FS 1265 Fluid 300 cSt

Fluorosilicone oil, useful as ingredient in lubricants and as active ingredient in antifoams for non-aqueous systems. Used in oil and gas separation, reclaiming of used chlorinated solvents after dry cleaning, solvent degreasing or solvent extraction operations, and suitable for foam control in solvent systems where conventional polydimethylsiloxane fluids are soluble and promote foam.

- Efficient and persistent antifoam
- Insoluble in chlorinated solvents
- Resistant to chemicals and oxidation
- Low surface tension
- High flash point

PART Nº	SIZE	COLOR	CASE / PALLET
4019160	500 mL Bottle	Clear	1 / 100
3141772	4.5 KG Pail	Clear	1 / 60
1325990	25 KG Jerry Can	Clear	1 / 10
4019161	250 KG Drum	Clear	1 / 4



## DOWSIL™ 550 Fluid

100% actives, polyphenylmethyldimethylsiloxane polymer fluid. Useful as a heat transfer fluid, in thermostat systems and as a base oil for high temperature lubricants

- Low volatility
- Serviceable in temperature range of -40°C up to 230°C in open systems, and up to 315°C in closed systems
- High flash point and viscosity index
- Excellent heat transfer characteristics
- Good compressibility
- Good oxidation and thermal stability

PART Nº	SIZE	COLOR	CASE / PALLET
2288494	500 mL Bottle	Clear	1 / 64
2076641	4 KG Pail	Clear	1 / 10
4019093	20 KG Pail	Clear	1 / 24
2639203	220 KG Drum	Clear	1 / 4



## DOWSIL™ 710 Fluid

Polyphenylmethyldimethylsiloxane fluid used for a variety of applications such as lubricant for timing devices, instruments, and bearings operating at 0°C to 260°C.

- Lubricant for timing devices, instruments, bearings operating at 0°C to 260°C
- Good base oil for high temperature greases thickened with molybdenum disulphide
- Heat exchange fluid in high temperature baths and in heat treating baths for metals

PART Nº	SIZE	COLOR	CASE / PALLET
2695707	4 KG Pail	Clear	1 / 48
4019122	20 KG Pail	Clear	1 / 24
4019123	225 KG Drum	Clear	1 / 4



## GREAT STUFF™ Heavy Duty Bamboo Work Wipes

GREAT STUFF™ Heavy Duty Bamboo Work Wipes' durable and strong scrub removes uncured GREAT STUFF™ and more. The 100% natural bamboo wipes clean up paint, oil, grease, and other messes.

- Removes uncured GREAT STUFF™
- Large sized 9.8 in by 7.9 in
- Removes oil, paint, grease, grime, and more
- Automotive, industrial, work, and household use
- 30 wet wipes per reusable package
- Made with 100% natural bamboo

Order by the case.

PART Nº	SIZE	CASE
7500104	Case	24 Packs
5900004	1/4 Pallet Display	8 Cases / 4 Displays Per Pallet



# GREAT STUFF™ Gloves

## GREAT STUFF™ Latex / Nitrile Blend Disposable Gloves

The 7.5 mil thick GREAT STUFF™ Latex / Nitrile Blend Disposable Gloves have the comfort and dexterity of latex and the durability and strength of nitrile. 100 pairs of gloves per box.

- 7.5 mil thickness provides industrial strength
- Puncture resistant
- Nitrile and latex blend blue disposable gloves
- Powder-free and polymer-coated

PART Nº	SIZE	EACH	CASE
5000089	L 100 Shelf Ready Case	100 Gloves	10 Boxes
5000090	XL 100 Shelf Ready Case	100 Gloves	10 Boxes
5900005	L 10 Shelf Ready Case	10 Gloves	20 Packs
5900002	1/4 Pallet Display	80 Boxes	8 Cases



## GREAT STUFF™ Insulating Foams

GREAT STUFF™ Insulating Foam Sealants are ready-to-use, polyurethane foams that fill, seal, and insulate gaps. Offers airtight, water-resistant, long-lasting seals via high-yield, no-drip dispensing systems.

- Wide variety of GREAT STUFF™ options including Gaps & Cracks, Big Gap Filler, Fireblock, Window & Door, Pestblock, and Multipurpose Black
- Available in smart dispensers, standard straws, and gun cans
- Paintable, sandable, and stainable
- Tack free in 10-15 minutes
- Cost-effective



# FROTH-PAK™ Foams

# FROTH-PAK™

## FROTH-PAK™ Foam Sealants

Two-component, chemically-cured polyurethane foam that comes either as a sealant or Class A fire-rated insulation. Designed for professional use.

- Expands quickly to fill cavities, penetrations, and gaps greater than two inches
- Helps improve the comfort, health, performance, and energy efficiency of any building
- Offers lower long-term cost of ownership compared to drum and rig systems
- Provides continuous barrier against air filtration and helps seal out moisture, dust, pests, and smoke

PART N°	PRODUCT	SIZE	CASE / PALLET
12030014	Froth-Pak 12	Kit	1 / 144



## LENTEK™ Insulating Foam Sealant

Fills and insulates gaps efficiently with the power of long-lasting, water-resistant, expanding foam. Provides a simple, cost-effective solution to eliminate unwanted airflow and improve energy efficiency.

- Triple expanding
- Cost-effective polyurethane foam sealant
- UL Listed
- Interior/exterior use
- Long-lasting, airtight, and weather-resistant seals
- Adheres to wood, metal, masonry, glass, and most common building materials

PART N°	SIZE	COLOR	CASE / PALLET
2299120	12 OZ Straw	Tan	12 / 912



## LENTEK™ Fireblock Foam Sealant

Fills and insulates gaps efficiently with the power of long-lasting, water-resistant, expanding foam. Orange-colored foam for easy identification and inspection.

- Impedes spread of fire and smoke through service penetrations
- Cost-effective polyurethane foam sealants
- UL Listed
- B2 Fire Rating
- Seals service penetrations between floors and electrical runs through wall studs
- Adheres to wood, metal, masonry, glass, and most common building materials

PART N°	SIZE	COLOR	CASE / PALLET
2299121	12 OZ Straw	Orange	12 / 912





## Lucas Oil Red “N” Tacky Grease

Smooth, tacky, red lithium complex grease fortified with rust and oxidation inhibitors. Can be used in many general agricultural, automotive, and industrial applications.

- NLGI #2
- Water-resistant
- Excellent mechanical stability
- Long storage life
- Fortified with rust and oxidation inhibitors
- Enhanced tackiness enables longer performance

PART Nº	SIZE	COLOR	CASE / PALLET
11025	11 OZ Aerosol	Clear	12 / 1,296
10005-30	14 OZ Cartridge	Red	30 / 1,800
10574	1 LB Tub	Red	12 / 1,200
10027	35 LB Pail	Red	1 / 48
10028	120 LB Keg	Red	1 / 9
10029	400 LB Drum	Red	1 / 4



## Lucas Oil X-TRA Heavy Duty Grease

EP fortified grease that exceeds OEM specifications and is virtually wash-out-proof. Formulated for automotive, agricultural, heavy-duty, and industrial applications.

- NLGI #2
- Enhanced stability compared to conventional lithium grease
- Last four times longer than regular grease
- The ultimate grease for high-speed bearings
- Fortified with an extreme pressure additive package

PART Nº	SIZE	COLOR	CASE / PALLET
10330	1 LB Tub	Green	12 / 1,200
10301-30	14.5 OZ Cartridge	Green	30 / 1,800
10305	35 LB Pail	Green	1 / 48
10316	120 LB Keg	Green	1 / 9
10335	400 LB Drum	Green	1 / 4



## Lucas Oil Marine Grease

Premium, multi-purpose, OBSC grease containing unique polymers, anti-wear agents, and tackifiers with inherent rust and oxidation resistance to provide the highest-performance properties.

- NLGI #2
- Excellent fresh water and salt water corrosion protection
- Extreme pressure properties, water-resistance, and shock-loading protection
- Applications include trailer wheel bearing, trailer chassis lubrication, and outboards
- Crossover applications in automotive wheel bearing and chassis lubrication
- Overbased Calcium Sulfonate (OBSC)

PART Nº	SIZE	COLOR	CASE / PALLET
11148	1 LB Tub	Blue	12 / 1,200
10320-30	14.5 OZ Cartridge	Blue	30 / 1,800
10321	35 LB Pail	Blue	1 / 48
10322	120 LB Keg	Blue	1 / 9
10660	400 LB Drum	Blue	1 / 4



## Lucas Oil White Lithium Grease

Multi-purpose, high-quality NLGI #2 formulation. Recommended for use in household applications including garage doors, hinges, openers, and springs.

- NLGI #2
- White and creamy in appearance
- Long-lasting and reduces wear
- Extreme friction reducer

PART Nº	SIZE	COLOR	CASE / PALLET
10533	8 OZ Tube	White	12 / 840
10535	35 LB Pail	White	1 / 48



## Lucas Oil Hydraulic Oil Booster & Stop Leak

One-of-a-kind, long-lasting blend of oils and petroleum extracted additives that add lubricity and thermal stability to any hydraulic oil. Excellent preventative maintenance product, adding life to pumps, rams, seals, and the treated hydraulic fluid.

- Designed for and unsurpassed at correcting existing problems
- Treat rate for preventative maintenance is only 5-10%
- Anti-foam agents present

PART Nº	SIZE	CASE / PALLET
10019	1 Quart	12 / 840
10018	1 Gal	4 / 240
10039	5 Gal Pail	1 / 48
10040	55 Gal Drum	1 / 4



## Lucas Oil Industrial Gear Oils

Blended with the highest-quality base oils and additives to provide extreme pressure protection, resistance to foam, and excellent rust, corrosion, and oxidation protection.

- Excellent shock-loading properties
- Designed to withstand heavy loads
- Non-corrosive to brass, bronze, steel, and other copper alloys
- Recommended for use in bevel, spur, herringbone, planetary, worm, and industrial hypoid gears
- Available in gallon bottles, 5 gal pails, 6 gal boxes, 55 gal drums, and totes

PART Nº	PRODUCT	SIZE	CASE / PALLET
10673	ISO 150	55 Gal Drum	1 / 4
10590	ISO 220	55 Gal Drum	1 / 4
10592	ISO 320	55 Gal Drum	1 / 4
10806	ISO 460	55 Gal Drum	1 / 4
10496	ISO 680	55 Gal Drum	1 / 4



## Lucas Oil Penetrating Oil

Designed to loosen rusted-on nuts and bolts, finding its way between the tiniest of crevices between metal parts and lubricating them.

- Fortified with powerful corrosion inhibitors and wetting agents
- Slow evaporation that leaves a tenacious film that fights water and corrosion
- Use in any position, even upside down
- Use on: nuts, bolts, hinges, bearings, sliding doors, bicycle chains and a million other uses around the home, garage, shop, and office

PART Nº	SIZE	CASE / PALLET
11043	11 OZ Aerosol	12 / 1,296



## Lucas Oil Multi-Purpose Parts Cleaner & Degreaser

Made with advanced Polyetheramine (PEA) detergents to help clean and degrease carburetors, chokes, brake calipers, rotors, air intakes, throttle bodies, and unpainted metal parts.

- Removes build-up that can cause loss of power, rough idle, high emissions, and hard starting
- Fast-drying and helps remove unwanted deposits such as gum, varnish, oil, brake fluid, grease, dirt, and sludge
- Cleans brakes for better performance and smoother operations
- 50 state VOC compliance

PART Nº	SIZE	CASE / PALLET
11115	16 OZ Aerosol	12 / 1,080
11115-6	16 OZ Aerosol	6 / 540





# LENTUS



5/2025



DU PONT

DOWSIL™

DOWFROST™

FROTH-PAK™

GREAT STUFF

LUCAS OIL



LentusLLC.com

Sales@LentusLLC.com

+1-270-765-2212

400 Ring Road, Suite 101  
Elizabethtown, KY 42701