

# 10MSP

MOBILE STOCK PICKER



## Performance

Platform Height	10 ft	3.05 m
Working Height	16 ft	4.88 m
Drive Height	Max. Platform Height	
Stowed Height	57 in.	145 cm
Platform Entry Height	13.75 in.	35 cm
Platform Size (W x L)	20 x 27 in.	49.5 x 69 cm
Overall Vehicle Length		
Chassis Length	61 in.	155 cm
Overall Vehicle Width		
Chassis Width	32.5 in.	83 cm
Chassis Width (without bumper)	29.5 in.	75 cm
Gross Vehicle Weight	1,100 lb	499 kg
Capacity		
Platform	350 lb	159 kg
Carry Deck	250 lb	113 kg
Material Tray	250 lb	113 kg
Max. Drive Speed		
Platform Lowered	5.0 mph	8.0 km/h
Platform Elevated	0.5 mph	0.8 km/h
Turning Radius	Zero	
Gradeability	15%	
Underclearance	2 in.	5 cm

## Standard Specifications

### Power Source

Batteries	4 Sealed 210 amp-hr Maintenance Free (AGM)	
Battery Charger	25 Amp Automatic	
Drive System	4 Brush Direct Electric (planetary gear)	

### Tires

Rear Drive & Steer Wheels	12.62 x 4 in.	32 x 10 cm
Non-Marking Front Caster Wheels	8 x 2.5 in.	20 x 6 cm



## Standard Features

- Heavy Duty Planetary Gear Drive Motors
- Simultaneous Lift and Drive Capability
- Point & Go® One-Hand Drive and Steer System
- Proportional Drive
- Automatic Five-Hour Battery Charger
- Battery Discharge Indicators — Platform and Base
- Lubrication-Free Anodized Aluminum Mast Sections
- Maintenance-Free Mast Guide System
- Strobe Lights Front and Rear
- Programmable Motion Alarm
- Slope Cut-Out Control Interlock
- Stand-On Foot Switch Operation Enable Control
- Platform Gate Operation Interlock
- Adjustable Height Material Tray
- Non-Marking Tire Material
- Lanyard Attachment Anchor Point
- Hourmeter
- Horn
- Shipping Skid
- Transportation Tie Downs
- Side and Front Bumpers
- ANSI, OSHA & CSA Compliant

## Accessories & Options

- Charger Cord Retractor
- Programmable 4-Digit Security Lock
- Guide Roller System
- Remote Manual Descent
- Object Sensing Pad
- Electrically-Powered Material Tray (200lb Capacity)
- Rubber Floor Mat

## The JLG "1 & 5" Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

Part No.: 3132119  
R1219\_A92.20  
Printed in USA



### JLG Industries, Inc.

1 JLG Drive  
McConnellsburg, PA 17233-9533  
Telephone 717-485-5161  
Toll-free in US 877-JLG-LIFT  
Fax 717-485-6417  
[www.jlg.com](http://www.jlg.com)

An Oshkosh Corporation Company