



making work easy

**UNICORN  
DenMart** ®  
Behind The Best Indian Dentists



**SILENT Compact CAM Suction**  
**SILENT powerCAM EC Suction**

## SILENT Compact CAM Suction

A SILENT SUCTION COMPACT CAM from Renfert Germany specially designed for your cam functioning. It's an silent dust collector suction which collect waste powder from your milling machine specially zirconia. Its an compact bag free extraction unit specially for compact dental cam units.

### Advantages

- ✦ Bi-directional communication between extraction unit and CAM unit thanks to the PLC interface.
- ✦ Low operating noise of max. 55 dB(A).
- ✦ 3x longer service life in comparison to conventional collector motors (1000 operating hours guaranteed).
- ✦ No follow-up costs due to bag-free dust collection.
- ✦ Working without interruption due to uncomplicated motor change within minutes.



### Technical Specifications

<b>Permissible Mains Voltage / Frequency</b>	230–240 V, 50/60 Hz
<b>Nominal Voltage</b>	230 V
<b>Suction Turbine Power</b>	490 W (230 V)
<b>Volume Flow (Max.)</b>	2500 l/min (1.47 ft³/s)
<b>Filter Quality</b>	Class M According To EN 60335-2-69
<b>Cam Interface</b>	RJ 45 Socket
<b>PLC: Input Signal / Output Signal 2 x Turbine ON/OFF / 2 x Status Information Sound Pressure Level (LpA)</b>	At Max. Volume Flow 55 dB (A)
<b>Fill Level Dust Collector</b>	~ 2.6 l (0.69 gal)
<b>Weight (Empty)</b>	~ 13.2 kg (29.1 lbs)
<b>Dimensions (W x H x D)</b>	245 x 440 x 500 mm (9.6 x 17.3 x 19.7")



**With PLC Interface Cable  
for Better Performance  
of Suction Motor**

## SILENT powerCAM EC Suction

Extraction units for CAM systems

Powerful, bag-free extraction unit with automatic filter cleaning and EC motor technology for heavily used CAM units.

### Advantages

- ✦ Bi-directional communication between extraction unit and CAM unit thanks to the PLC interface
- ✦ Low operating noise of max. 54.3 dB (A)
- ✦ Reliable production process through brushless EC motor technology (guaranteed runtime of 5000 operating hours)

### Details

- ✦ High volume flow of approx. 4000 l/min
- ✦ No follow-up costs due to bag-free dust collection
- ✦ Safe disposal of fine milling dust with the help of a disposal bag



### Technical Specifications

Permissible mains voltage	220–240 V   120 V   100 V
Permissible mains frequency	50/60 Hz
Power consumption	1610 VA (230 V)   1440 VA (120 V)   1250 VA (100 V)
Volume Flow (Max.)	3984 l/min // 2.34 ft³/s
Max. depression	257 hPa   262 hPa   255 hPa // 3.73 psi   3.8 psi   3.7 psi
Filter quality	Class M according to EN 60335-2-69
CAM interface	RJ 45 socket
Number of suction hoses	1
Sound pressure level (LpA) (at max. volume flow)	54.3 dB (A)
Weight (empty)	~18 kg // ~39.7 lbs
Dimensions (W x H x D)	270 x 535 x 540 mm // 10.6 x 21.1 x 21.2"
Ø suction fittings interior	42 mm // 1.65"
Fill level dust collector	~7 l // ~1.85 gal



Tool-free filter & motor change possible in a few minutes



With PLC Interface Cable for Better Performance of Suction Motor



WHERE **TRUST** COMES **FIRST**



**Warranty Ke Saath Bhi  
Warranty Ke Baad Bhi**

### For Sales Queries

 85277 00805

 [cadcamcrm@unicorndenmart.com](mailto:cadcamcrm@unicorndenmart.com)

### Customer Care

 011-45551250, 95994 48518

 [care@unicorndenmart.com](mailto:care@unicorndenmart.com) | [care1@unicorndenmart.com](mailto:care1@unicorndenmart.com)



SCAN TO VISIT OUR WEBSITE



Corporate Office: 3 Local Shopping Centre, MOR Land, Near J Block DDA Market,  
New Rajender Nagar, New Delhi – 110060

    /unicorndenmart.com

\* Accessories shown may not be a part of standard equipment. Specifications are subject to change without notice.

Ver 3/2025