A SAFE HARBOR IN AN OCEAN OF THREATS SMART PORT & MARITIME SOLUTION

SION

14 100

WITH HIKVISION AS YOUR PARTNER, YOU WILL STAND ON A SOLID FOUNDATION.

Hikvision is a world leading provider of security products and solutions. Featuring an extensive and highly skilled R&D workforce, Hikvision manufactures a full suite of comprehensive products and solutions for a broad range of vertical markets. In addition to the security industry, Hikvision extends its reach to smart home tech, industrial automation, and automotive electronics industries to achieve its long-term vision. Hikvision products also provide powerful business intelligence for end users, which can enable more efficient operations and greater commercial success. The outstanding capabilities and performance of Hikvision in the security and video surveillance industries have been recognized by leading analyst firms and global awards.



From the early digital age to today's intelligence era, we have seized every opportunity to advance the industry with our innovative technologies.


Hikvision's core technologies include: visual perception, cloud storage, big data, cross-media perception and reasoning, video codec, streaming media networking and management, audio and video data storage, embedded systems development.

As the pioneer in AI technology, Hikvision established an algorithm team for AI technology research in 2006. During this decade, Hikvision first launched deep learning-based servers then expand to a comprehensive range of AI products in 2016. Based on the continually researches and practices, Hikvision developed the AI Cloud structure and ranked No.1 in various global Artificial Intelligence contests.



A GLOBAL BRAND WITH A LOCAL PRESENCE

The customer comes first at Hikvision. Long-lasting partnerships are fostered as Hikvision works with its customers to identify their needs and provide solutions that support their success. Hikvision continues to expand into new areas and markets and currently has 21 regional offices in countries around the world. 65% of Employees in Hikvision's International Business Department are locals working in their native regions. Hikvision's support team of regional sales managers, sales engineers, and technical service personnel all share the same goal of helping customers with their individual needs.



EXPLORE VERTICAL SOLUTIONS TOGETHER WITH HIKVISION

As a solution partner with the world's largest CCTV equipment provider, you will enjoy:

- Platform/software integration support
- Extensive customization support
- Local support by Hikvision overseas subsidiaries
- Technical project support from Hikvision's R&D
- Possibilities for co-marketing cooperation
- New product/solution introduction
- New product demo support
- Yearly site visit for technology/product exchange
- Information Sharing via Solution Partner Platform



SMART SOLUTION FOR PORT & MARITIME

The importance of security in seafaring trades is matched only by its urgent vulnerabilities. And with the number of seaport shipments annually extending well into the millions, only a small fraction are individually inspected. Hikvision aims to change that.


Hikvision's Smart Port & Maritime Solution enables the early detection of security threats. Hikvision's technologically superior cameras capture even the minutest details, and in the harshest conditions. Our recording devices accurately and reliably store and replay crucial security-related information. We want to help you put into place effective plans and procedures for your crucial security needs.


Hikvision's advanced solution enables authorities to efficiently meet the requirements of the International Ship and Port Facility Security (ISPS) Code with top-tier performance. Our products arm you with the latest and highest quality surveillance, access control, and intelligence-gathering equipment. Hikvision's solution covers all your needs for monitoring the movement of personnel and cargo and for ensuring security communications with the utmost stability and reliability.

- Ensures around-the-clock perimeter safety
- Increases vehicle access management
- Protects valuable merchandise
- Records reliable footage for investigation












Parking & Warehouse • Excellent imaging in low-light conditions

• Single wide angle lens monitoring covers entire areas





Vehicle Access Control ANPR for Vehicle event recording and entrance automation



On-Board Monitoring

Varied systems for a diversity of vehicles such as heavy duty trucks, container tankers, and coast guard vessels



Security Center

- System reliability
- Data safety
- Prompt event response




Perimeter Protection Durable cameras resist corrosion and provide long range detection of unauthorized objects

VEHICLE ACCESS CONTROL

Hikvision Vehicle Access system combines high quality ANPR cameras and back-end devices to create barrier linkage, B/W list filtering, and alarm triggering.

ANPR Cameras: HD video quality, weather-proof, ultra low-light capability, barrier linkage support





* The exact functionalities may vary based on local strategy and product development.

Hikvision ANPR System • License Plate Auto Comparisor

- B/W list Filtering
- Alarm Triggering
- Result Query
- Result Export
- ANR (Auto Network Recovery)
- ANPR Remote configuration




* ANPR support requires a customized process, and the availability of regional Hikvision LPR support varies based on local algorithm development.

PARKING AREA MONITORING

Hikvision has developed a complete product line to monitor large areas and detect suspicious targets, even in low light conditions. Additionally, the iVMS platform and LED indicators manage and display the availability of public parking.

Panoramic Cameras: Four innovative Darkfighter imagers can deliver panoramic views with ultra low light capability to cover entire parking areas.






PERIMETER PROTECTION

Ports are vast outdoor areas, full of valuable merchandise. Therefore, thermal imaging cameras are preferable, since these help detect intrusion at extended distances for improved security.

Dual-Lens Thermal Camera: One thermal imaging lens suffices for long-range detection, while a another, single Darkfighter visual imaging lens renders detailed video footage. Both work together in one camera housing.






ON-BOARD MONITORING

From Stainless Steel Darkfighter Cameras to mini vehicle cameras to vibration-resistant mobile encoders, Hikvision offers a complete line of products to meet diverse surveillance needs, including container tankers, coast guard vehicles, and heavy duty trucks.

- Container Tanker: Darkfighter Stainless Steel cameras + mobile IP
 recorder
- Coast Guard Vessels: Stainless Steel mini dome + mobile IP recorder
- Heavy Duty Trucks: HD IP or HD TVI on-board system for truck tracking and incident recording






SECURITY CENTER

Comprising all the important video footage of daily operations, bank office's security center is a core of total CCTV system that requires utmost reliability and manageability for data protection and alarming operations.

- Embedded NVR: Hikvision has the richest embedded network recorder product line from 4 channels to 256 channels for every level of need
- Video Management Platform: HikCentral is the CCTV system core that manages, views, plays back, and controls all the daily operations among all devices
- Network Storage Server: A must-have product line for total secure data storage
- Monitor Display System: From standalone monitors to large TV walls, Hikvision has it all








Disconnected

Auto Network Recovery (ANR)

- Auto backup if network connection is interrupted
- Data moves from SD card to back-end device while network connection is restored
- We recommended using Hikvision brand Micro SD card for ANR storage




Data Safety RAID & N+1 Failover

- Single-spot storage backup:

Multi-RAID supported by embedded NVR and Storage Server


- Multi-spot storage backup:

When any active NVR is out of service, the standby NVR can take over recording automatically




Alarm Management Multi-users Notification

- Real-time alarm notifications sent to HikCentral control clients
- Even mobile clients can receive notifications
- One-Check-All mechanism allows one user to handle the event and others to simply receive notification



Large Data Management Smart Backup

- Supports event footage backup
- Saves maximum storage space



Large Data Management Smart Search

- Fully compatible with Hikvision Smart IP Cameras
 Easy and quick event search for snapshots and video recording
- Plays back the target event footage at standard speed and can fast-forward (up to 64x)
- Unrelated video can be skipped during playback





• DarkFighter ultra-low light technology

• 1/1.8" progressive scan CMOS sensor

• License Plate Recognition

• Full HD1080p, up to 60fps

Up to 256 GB on-board storageMotorized lens with Smart Focus

Full smart feature-setUp to 50 m IR range

• 140dB WDR

DS-2CD7A26G0/P ANPR Camera

DS-2TD2836-25/50

Bullet Camera

Thermal + Image Dual Lens



DS-2CD6984G0 32 MP 180° Panoramic Network Camera

- 4 x 1/1.8" CMOS sensors
- 8160 × 3616 realtime video output
- 180° horizontal panoramic view
- Four IR LEDs with up to 20 m IR distance

Thermal Imager

- Vanadium oxide uncooled focal plane arrays
- Up to 384 x 288 resolution
- 25 mm lens, FoV: 14.88° or 50 mm lens, FoV: 7.47°
- Smart Detection: Intrusion detection, Line Crossing detection, Region Entering/Exit detection

Visual Imager

- 1/2.8" progressive scan CMOS
- DeepinView
- Up to 1920 x 1080 resolution
- 100 m IR range
- 13 mm / 25 mm fixed lens

General

- Support on-board storage, Micro SD/SDHC/SDXC (card no included)
- Audio I/0: 1/1; Alarm I/0: 2/2
- Protection: IP66
- Built-in heater
- AC24V, max 22W
- -40°C~ 60°C working temperature



DS-2TD4136-25(50) Thermal + Image Dual Lens PTZ Camera

Thermal Imager

- Vanadium oxide uncooled focal plane arrays
- Up to 384 x 288 resolution
- 25 mm lens, FoV: 15° x 11° or 50 mm lens, FoV: 7.47° x 5.61°
- Smart Tracking: Panorama tracking, Event tracking, Multi-scene Patrolling
- Smart Detection: Intrusion detection, Line Crossing detection, Region Entering/Exit detection

Visual Imager

- 1/1.9 progressive scan CMO
- Up to 1920 x 1080 resolution
- 200 m IR range
- Pan: 360°endless; tilt: -15°~ 90°

General

- Support on-board storage, Micro SD/SDHC/SDXC (card no included)
- Audio I/0: 1/1; Alarm I/0: 7/2
- Protection: IP66 protection
- Built-in heater
- AC24V, max 60W
- -40°C~ 60°C working temperature



DS-2CD6626B-IZHS

2 MP Anti-Corrosion Bullet Camera

- H.264 / H.264+ / H.265 / H.265+
- 2 MP realtime resolution
- 120 dB WDR
- ATEX, IECEx, IP67
- 316L Anti-Corrosion Standard: NEMA 4X, C5-M
- Support on-board storage, up to 128GB
- AC 24V to 240V



DS-M5504HNI 4-Channel Mobile NVR

- Supports 4 channels of 1080P IP video input
- 4-channel POE interface
- Pluggable disk box with vibration damping technology
- 2 x pluggable 2.5-inch HDDs / SSDs
- 1 x SD/SDHC card slot
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification



DS-2CD6626DS-IZ(H)S Corrosion-Resistant Network Camera

- Ultra-low illumination technology
- 316L stainless steel housing
- 1/1.8" progressive scan CMOS sensor
- 2.8~12 mm motorized VF lens
- 120 dB WDR
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification



DS-M7508HNI (/GW/WI) On-board Network Recorder

- 1920 x 1080 high resolution
- Support 8-ch IP video with PoE interfaces
- Pluggable 3G module optional (/GW)
- Built-in Wi-Fi / GPS optional (/WI)
- Support two 2.5-inch HDDs / SSDs
- Hard disk box with USB interface supporting intelligent temperature control and data export
- M12 connectors ensuring signal stability
- Wide-range power input (+8VDC ~+36 VDC)
- Power-off protection avoiding data loss
- Aluminum die-cast chassis with no fan design well adaptable to working environment



DS-2XM6726FWD-I 2 MP IR Mobile Dome Network Camera



DS-2XM6522WD-I 2 MP Outer-vehicle Mini Dome Network Camera

- 2.0/2.8/4/6/8 mm fixed lens
- Up to 30 m IR range
- IP67, IK10 weather-resistant
- H.265, H.265+

- Special design for vehicle-mounted
- 2 MP real time resolution
- 3-axis adjustment
- M12 Ethernet interface(optional)
- Up to 10 m IR range
- IP68, IK10
- EN50155, EN50121 certification



DS-2XM6425G0/F-IM81

7-inch TFT-LCD screen

DS-MP1301

2 MP Mobile Covert Camera

PRODUCT SHOWCASE



DS-2XM6222FWD-I

2 MP Mobile Network Camera

- 2.8 mm, 4 mm, 6 mm, optional
- 1920 × 1080 resolution
- H.264, H.264+, H.265, H.265+
- 120 dB WDR
- IP67
- IR range: 10 to 30 meters



- 1920 × 1080 @ 30fps
- 120 dB WDR
- 3D DNR
- H.264, H.264+, H.265, H.265+



DS-96128/256NI-I16/I24(/H) Embedded Super NVR

- Maximum 576/768 Mbps bitrate Input
- Supports third party network cameras
- Up to 12 MP resolution recording
- H version support 64-ch 1080P decoding capability
- HDMI output at up to 4K resolution
- Supports redundant power supply
- Up to 16/24 SATA interfaces , up to 8 TB for each HDD,
- HDD hot swapping with RAID 0/1/5/6/10
- One LCD screen optional , mini SAS optional



DS-9632/64NI-I8 Embedded 4K NVR 4K

- Maximum 320Mbps bitrate Input
- 200 Mbps bitrate input (RAID enabled)
- Support 3rd party network cameras
- Up to 12 MP resolution recording
- Support H.264 / H.264+ / H.265 video format
- 2 x HDMI & 2 x VGA output (3840 x 2160)
- Support RAIDO, 1, 5, 10
- Support redundant power supply
- Dual digital network interfaces
- 8 x SATA, 1 x eSATA, 2 x USB2.0, 1 x USB3.0
- 19-inch rack-mounted 2U chassis



HikCentral Professional Video Management Platform

- Centralized device & user management
- Maximum connected devices per system: 1024
- Maximum 100 control client for system
- Support 3rd party integration via ONVIF & SDK
- Additional add-on modules:
- LPR: license plate recognition
- Transaction: POS integration + CCTV footage
- Business Intelligence: people counting, heat mapping and retail traffic analytic



DS-A81016S

Network Storage System

- High performance 64 bit RISC processor
- Up to 16 HDD, 6TB maximum capacity for each
- Up to 180-ch 4CIF real-time recording
- iSCSI/NFS/CIFS/FTP/HTTP/AFP protocols
- Support RAID 0, 1, 3, 5, 10, 50
- Support HDD hot-swapping
- Dual Gigabit network interfaces
- Modularized design for easy maintenance
- Redundant power design for high reliability



DS-A82024D Network Storage System

- High performance & easy extensible hardware platform
- Double controller system design
- Automatic service takeover
- Disk detection, repairing and RAID optimization
- Low power consumption
- 4U chassis structure, support up to 24 HDDs and cascade extension



DS-M5504HNI 4-ch Mobile NVR



DS-C10S-S09T/S11T/ S22T TV Wall Controller

- Up to 12 MP/14 fps resolution
- 1/4/6/8/9/16 division
- 1-ch DVI and 1-ch VGA signal input(Except DS-6401HDI-T)
- DS-6401 supports HDMI/VGA/BNC interfaces
- Other models support DVI/BNC interfaces (HDMI/VGA requires converter)
- PC signal to display on video wall
- Screen joint and display
- Cross-window video roaming
- Video fluency enhancement

- A signal source can be displayed on M \times N (M \geq 1, N \geq 1) display units
- Multiple signal input sources: VGA, DVI, HDMI, YpbPr, DP
- Built-in matrix, one signal displays on multiple windows
- Window division, splicing, roaming, cross-window
- Supports 1/4/9/16 window division modes and full screen window switching





- 46" or 55" screen dimension
- -NL: 500cd/ m² brightness
- -NH: 800cd/ m² brightness
- 3.5mm physical seam
- Defog, low-light compensation
- Edge processing, true native image
- Dynamic self-adaption noise reduction
- Cross color suppression
- Signal input: HDMI, DVI, VGA, BNC, YPbPr
- Signal output: DVI, VGA, BNC
- Remote control: IR in, Address ID
- RS232 control

DS-D2046NL-C DS-D2055NL-B/G Ultra Slim Bezel LCD



DS-D5032FL LCD Monitor

- 8 bit/10 bit 2-ch LVDS(1920*1080) Full HD1080P resolution
- Adopt 3D digital comb filter
- True color OSD and user-friendly operation menu
- Adopt mstar ACE-5 auto color and image enhancement angine, to improve image contrast, detail
- 1 channel HDMI 1.3 input interface support HDCP 1.2
- Support video output • Support audio I/O

• H.264 Video Compression • 3.5 inch IPS Touch Screen

• Up to HD1080p Video Recording

• Built-in 3G and GPS module

• Up to 32GB Micro SD card recording

• 5MP HD Camera

DS-6102 HLI/GW Portable Video Recorder



DS-1600KI Network Keyboard




- 10.1" TFT LCD touchscreen with 1024 × 600 resolution
- Live view and video playback
- Video wall control
- 4-axis joystick
- Controllable of 2000 devices
- Compatible with Hikvision IP cameras, DVR/NVR, decoder, matrix

MINIMIZE RISK AND MAXIMIZE BUSINESS RETAIL SOLUTION

HIKVISION

Follow us on social media to get the latest product and solution information



Hikvision

Hikvision Corporate Ch



ww.hikvision.com