

SELECT PRO WELD-IN LATCH DEADLOCK

Specification Sheet **SWLD**

FEATURES

- Enhanced security: Stainless steel latchbolt springs 13mm into the gate post and extends 30mm when deadlocked.
- Maximum strength: Welding the lock into the gate ensures the most secure installation method.
- Long-lasting durability: Features a brass latchbolt bearing for smooth, reliable operation over time.
- Precise fit: Adjustable latchbolt length allows for on-site customisation, and it can be rotated for left or right-handed gates.
- Handles sold separately



PRODUCT DETAILS

Product code	Description
SWLD1630	For 30mm (1-1/8") wide gate frames
SWLD1640	For 40mm (1-5/8") wide gate frames
SWLD1650	For 50mm (2") wide gate frames
SWLD1660	For 60mm (2-3/8") wide gate frames



INCLUDED IN THE BOX

- 1x3mm hex key
- Keep plate (self-drilling fasteners)
- M5 fixing bolts
- A set of keys (3)
- Latchbolt

INSTALLATION

1. Disassemble the lock by removing the 3 screws from the face plate of the lock, remove the face plate, and then remove the euro cylinder (twist the key 15 degrees clockwise or anti-clockwise to release). The insides of the lock will then slide out.
2. Weld the lockcase to the gate and galvanise or paint as part of the gate.
3. Fit the lock and eurocylinder into the lockcase and secure with screws.

MAINTENANCE: Every two months, lubricate the latchbolt with light oil. Annually, dismantle lock and spray the mechanism inside with light oil.

